

## NEC MultiSync® LCD2690WUXi




- Highly innovative LCD monitor with A-TW-IPS (Advanced True White IPS) TFT display
- Ultra-thin frame (18.8 mm)
- L-shape front button technology for intuitive OSD control
- ambix<sup>3</sup>™ Technology – safety of investment with analog/digital interfaces (DVI-I, DVI-D, VGA) with up to 3 inputs simultaneously
- Rapid Response technology 7 ms (grey-to-grey)
- RapidMotion feature guarantees smooth representation of moving images
- TileMatrix and TileComp features
- AutoBright technology
- AmbiBright: Ergonomics and power saving ambient light sensor
- OmniColor™: sRGB and 6-axis-colour-control
- ErgoDesign®: Height adjustable stand (130 mm)
- GammaComp: 12 bit LUT (look up table) and 12 bit gamma correction
- CableComp for best picture quality through automatic signal compensation of long cables and weak signals incl. Sync continuity detection
- ColorComp for best uniformity of brightness and colour
- TORO™ Design: Screen rotation 90° (portrait capability)
- Realtime clock with scheduler
- Low power consumption and EcoModes for reduced Total Cost of Ownership (TCO)



# NEC MultiSync® LCD2690WUXi **-Preliminary-**

Panel Technology	A-TW-IPS (Advanced True White IPS) TFT with a Colour Gamut of 92% NTSC (typ.)
Screen Size [inch/cm]	25.5/64.9
Pixel Pitch [mm]	0.287
Viewing Angle	178° horizontal / 178° vertical (typ. at contrast ratio 10:1)
Contrast Ratio (typ.)	800:1
Brightness (typ.) [cd/m <sup>2</sup> ]	400
Response Time (typ.) [ms]	7 (grey-to-grey), 13 (7 white / black; 6 black / white)
Colours [Mio.]	16.77
Horizontal Frequency [kHz]	31.5 - 91.1 and 118.4
Vertical Frequency [Hz]	50.0 - 85.0
Optimum Resolution	1920 x 1200 at 60 Hz
Other Resolutions	1200 x 1920; 1600 x 1200; 1280 x 1024; 1280 x 960; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	3 (Digital: 1 x DVI-D; Digital/ Analog: 1 x DVI-I; Analog: 1 x D-sub 15 pin)
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Auto Adjust; Colour Temperature Control; Fine Adjust (analog); Sharpness; Brightness; Contrast; Intelligent Power Management; Monitor Information; OmniColor™: sRGB and 6-axis-colour-control; Black Level; Expansion Mode; On-Screen-Manager (OSM) lock-out; Advanced NTAA (Advanced Non-Touch-Auto-Adjustment); Language Select; User Menu; Advanced User Menu; Hotkeys
Safety and Ergonomics	CE; TCO'03; TÜV ergonomic approved; TÜV GS; C-tick; GEEA/Energy label; Energy Star; FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; PCBC/B-mark; PSB
Power Requirements on Mode [W]	70 (max.)
Power Requirements Power-saving Mode [W]	1
Power Supply	100-120 V/220-240 V; 0.68 A/0.29 A; integrated power supply
Ambient Temperature (operating) [°C]	5 to 35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100 (4 points); 200 x 100 (5 points)
ErgoDesign®: Height Adjustable Stand [mm]	130 (Landscape)
Dimensions (W x H x D) [mm]	589.8 x 444.2 - 594.2 x 306.0
Screen Tilt / Swivel [°]	-5 to +30 / -170 to +170
Bezel Width [mm]	18.8
Cable Management	yes
Kensington Lock	yes
Weight [kg]	12.3
Specials	Adjustable power LED (colour and brightness); EcoModes; AmbiBright; AutoBright; Direct Brightness and Contrast; Auto Black Level; Auto Brightness; Auto Contrast; ambix <sup>3</sup> ™; CableComp with Sync Continuity Detection; ColorComp; Rapid Response; RapidMotion; TileMatrix; TileComp; OmniColor™; GammaComp (12 bit look up table) and 12 bit gamma correction; TORO™ Design; DDC-CI; NaViSet® and NaViSet® Administrator compatible; Real time clock with scheduler (Power-On and Power-Off timer); Overdrive; Advanced NTAA (Advanced Non-Touch- Auto-Adjustment); Self diagnostics; Quick release stand and handle
Audio Functions	Option: MultiSync® Soundbar 90
Colour Versions	Silver Front Bezel, Light Grey Back Cabinet; Black Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable DVI-A - VGA; Signal Cable DVI-D - DVI-D; CD-ROM; Sales Office List; User's Manual
Warranty	3 years warranty incl. backlight



All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. August 2006

see more.

NEC Display Solutions

[www.nec-display-solutions.com](http://www.nec-display-solutions.com)

NEC Display Solutions UK Ltd, 32 Southwark Bridge Road, London SE1 9EU

Phone: 0207 202 6300, e-mail: [infomail@nec-displays.com](mailto:infomail@nec-displays.com)

For further information on NEC products call: **08701 201 160**